

# **Excavator Hook**

# UKN - The Original Excavator Hook

Gunnebo Industries continuously works with product development and innovation to create the optimal solutions for each lifting situation. For more than 250 years we have developed products that have become today's standards on the market. There is however only one original – Gunnebo Industries. With the original you get the perfect fit and smart details.

Many excavators are used for material handling and lifting due to their availability at most work sites and capacity. However, often the rigging gear is attached either to the teeth of the bucket or on the arm directly, which together with no knowledge of capacity risk leading to accidents. This led Gunnebo Industries to develop the UKN hook back in 1975, an industry first.

## Tried & Tested Globally

The UKN has been fitted to excavators for over 40 years. Either as an aftermarket product or directly from the manufacturer. The UKN hook is the hook of choice for internationally leading manufacturers. With Gunnebo Industries' long experience, high quality and availability of both product and spare parts globally through our partners, the choice is easy.

#### 100% Proof-loaded

 Every hook individually proofloaded 3 x WLL


# Heavy-duty

- Drop-forged
- Rated with a 5:1 safety factor

## Clear markings

- Country of origin
- Traceability codes
- Model and WLL
- BG-approval stamp





# Universal Weld-On Hook, UKN

Art. no.	Code	WLL tonnes**	В	G	Н	K	L	Α	Х	Weight kgs
Z1002560	UKN-0,75*	0.75	20	13	20	19	81.5	5	56	0.2
Z6511810	UKN-1*	1.0	27	17	25	25	95	6	72	0.6
Z7009060	UKN-2*	2.0	33	20	30	30	114	8	86	0.9
Z6455730	UKN-3	3.0	30	23	32	35	132	10	105	1.3
Z6521160	UKN-4	4.0	30	29	38	42	140	11	114	2.0
Z6455800	UKN-5	5.0	34	30	47	45	165	12	131	3.2
Z6515390	UKN-8	8.0	34	40	51	50	172	13	133	3.6
Z6456030	UKN-10	10.0	47	43	58	55	220	14	170	8.2
Z1007850	UKN-15	15.0	55	50	67	60	240	15	188	9.8

<sup>\*</sup> Welding plate slightly curved

Fulfills requirements in: EN 474-1.

<sup>\*\*</sup> Safety factor 5:1