

pewag VLWP 2/4 Oversize master link assembly

Asymmetrically precise.

The new oversize lifting eye stands out for its asymmetrical shape and is suitable for the assembly of II- and IV-leg chain slings, both in the assembled and in the welded system.

The improved design of the upper curve optimises the contact surface of the assembly on the single hook, manufactured according to DIN 15401. The great plus of this master link assembly is the geometry of the lower area, which allows for the simple and quick assessment of the angle of the inclination, thus greatly increasing safety and efficiency during day-to-day operations and making miscalculations a thing of the past.

Extra-large rings make this master link assembly the perfect partner for crane hooks according to DIN 15401 up to no. 25. The assembly comes with CE-marking and is manufactured according to EN 1677-4, with mechanical values according to G12.



VLWP 2/4 Oversize master link assembly	Code	Consisting of	Can be used up to single hook according to DIN 15401 no.	Load capacity 0°-45° [kg]	e [mm]	d [mm]	t [mm]	w [mm]	d1 [mm]	t1 [mm]	w1 [mm]	Weight [kg/pc.]	For 2-leg slings	For 3- and 4-leg slings
	VLWP 2-7/8	LWP 22 + 2 BWP 13	25	4,250	394	23	340	155	13	54	25	3,6	7/8	-
	VLWP 2-10/4-7/8	LWP 26 + 2 BWP 16	25	7,100	410	27	340	155	17	70	34	5,2	10	7/8
	VLWP 2-13/4-10	LWP 32 + 2 BWP 20	25	11,200	425	33	340	155	20	85	40	8,00	13	10
	VLWP 4-13	LWP 36 + 2 BWP 26	25	17,000	480	38	340	155	27	140	65	12,8	-	13
	VLWP 2-16	LWP 36	25	17,500	340	38	340	155	-	-	-	8,9	16	-
	VLWP 4-16	LWP 40 + 2 BWP 32	25	26,500	490	40	340	155	33	150	70	16,3	-	16