



Drejelige/w. Swivel:

Transportruller, type DK**Type 1500-4D
Nylon****Type 4000 D
Nylon****Type 6000 D / 12000 D / 12000 D/C
Nylon / Stål/Steel / Composit/Composite**

DK Transportruller tilbyder et bredt og fleksibelt program af transportruller i høj kvalitet. Transportrullerne er udført i specialstål og forsynet med kuglelejer med høje bæretal i både drejeskammel og hjul, hvilket giver garanti for sikker transport og lang levetid. Gummibeklædte bæreflader. Alle DK Transportruller er på bærefladerne forsynet med et lag 8 mm skridsikret vaffelgummi, som forhindrer, at lasten rutsjer under transport. Lav placering af bærehåndtag giver ekstra sikkerhed. Bærehåndtagene på alle DK Transportruller er placeret min. 25 mm under bærefladen, hvilket forebygger risikoen for klemskader på brugerens hænder.

**Type 4000 DP
Nylon****Cargo skates, type DK**

DK Cargo skates offer a wide and flexible transport roller programme of high quality. The transport rollers are manufactured in special steel and provided with ball bearings with a high strength of lifting in both swivelling balster and in the rollers, which guarantees a safe transport and a long lifetime. Rubber covered supporting surface. All DK Cargo skates are supplied with a cover of 8 mm non-slip chequered rubber on the supporting surface, which prevents sliding of the load during the transport. Low placing of the carrying handles guarantees more safety. The carrying handles of all DK Cargo skates are placed minimum 25 mm under the bearing surface, which prevents the risk of damaged hands.

LEHAKA
SMEDE- OG MASKINFABRIK
Egenproduktion
In-house production

Varenr. / Item no.	Model	Type	Belastning / Capacity kg	Ruller / Rollers	Ruller / Rollers pcs	Rulle dim. / Roller dim. mm	Højde / Height mm	Bæreflade / Plate mm	Vægt / Weight kg
792-010-1151	Drejelig / w. Swivel	1500-4D	1500	Nylon	4	81 x 68	115	400 x 400	16
792-012-1401	Drejelig / w. Swivel	4000 D	4000	Nylon	4	85 x 90	115	200 x 200	15
792-019-1402	Drejelig / w. Swivel	4000 D/C	4000	Composit / Composite	4	85 x 90	115	200 x 200	15
792-013-1401	Drejelig / w. Swivel	4000 DP	4000	Nylon	4	85 x 90	115	240 x 160	22
792-014-1601	Drejelig / w. Swivel	6000 D	6000	Nylon	8	81 x 68	125	400 x 300	49
792-024-1123	Drejelig / w. Swivel	12000 D	12000	Stål / Steel	8	81 x 68	125	400 x 300	60
792-022-1122	Drejelig / w. Swivel	12000 D/C	12000	Composit / Composite	8	81 x 68	125	400 x 300	53
792-011-1201	Fast / Fixed	2000 F	2000	Nylon	2	85 x 90	105	180 x 105	5
792-011-1202	Fast / Fixed	4000 F/C Mini	4000	Composit / Composite	2	85 x 90	105	180 x 105	6,5
792-015-1401	Fast / Fixed	4000 F	4000	Nylon	4	85 x 90	105	220 x 170	10
792-016-1601	Fast / Fixed	6000 F	6000	Nylon	6	85 x 90	105	260 x 230	14
792-017-1803	Fast / Fixed	8000 F	8000	Stål / Steel	4	85 x 90	105	220 x 170	16
792-020-1802	Fast / Fixed	8000 F/C	8000	Composit / Composite	4	85 x 90	105	220 x 170	10
792-023-1123	Fast / Fixed	12000 F	12000	Stål / Steel	6	85 x 90	105	260 x 230	26
792-021-1122	Fast / Fixed	12000 F/C	12000	Composit	6	85 x 90	105	260 x 230	18

**Type 2000 F Nylon****Type 4000 F Nylon / 8000 F Stål/Steel****Type 6000 F Nylon / 12000 F Stål/Steel /
12000 FC Composit/Composite**



Transportruller, type DK

3 forskellige typer hjul

DK Transportruller produceres med tre forskellige typer hjul. Ved valg af transportruller skal man derfor være opmærksom på, hvor stor en last rullerne skal transportere og på hvilket underlag transporten skal foregå.

Nylonhjul er en løsning til lettere transportopgaver på jævne og rene overflader.

Stålhjul er løsningen til transport af tunge laster på rå betongulve eller lignende robuste overflader.

Composithjul er den flexible løsning til transport af laster i alle størrelser på overflader af enhver art.

Sammenbygning medfører nye muligheder

Alle DK Transportruller type F kan sammenkobles med 25 mm stålrør, hvorved man kan opnå en næsten uendelig forøgelse af rullernes kapacitet, ligesom sammenkobling sikrer at rullerne kører parallelt.

Cargo skates, type DK

Three different types of rollers

DK Cargo skates are produced with three different types of rollers. Choosing your transport rollers, be aware of the weight of the load to be transported and of the floor surfaces.

Nylon rollers are a solution for easy transports on level and clean surface.

Steel rollers are the solution for transporting of heavy loads on raw concrete floors or similar robust surfaces.

Composit rollers are the flexible solution for transporting of loads of all dimensions on all kind of surfaces.

Incorporation result in new possibilities

All DK Cargo skates can be coupled together with 25 mm steel tubes, which make it possible to attain to a nearly infinite increasing of the capacity of the rollers, just as an incorporation ensures that the rollers are driving parallelly.



Max. 5 ton Nylon
Bestående af / Consisting of:
1 stk. 792-012-1401 – 4000 D
2 stk. 792-011-1201 – 2000 F



Max. 8 ton Nylon
Bestående af / Consisting of:
1 stk. 792-012-1401 – 4000 D
2 stk. 792-015-1401 – 4000 F



Max. 10 ton Nylon
Bestående af / Consisting of:
1 stk. 792-012-1401 – 4000 D
2 stk. 792-016-1601 – 6000 F



Max. 15 ton Nylon
Bestående af / Consisting of:
1 stk. 792-014-1601 – 6000 D
2 stk. 792-016-1601 – 6000 F



Max. 30 ton Stål/Steel
Bestående af / Consisting of:
1 stk. 792-024-1123 – 12000 D
2 stk. 792-023-1123 – 12000 F



Max. 30 ton Composit/Composite
Bestående af / Consisting of:
1 stk. 792-022-1122 – 12000 D/C
2 stk. 792-021-1122 – 12000 F/C